



Archived resources

For further resources and
documentation please visit us:
www.cinos.net

Specifications

DXP HDMI Series

NOTE: *Appropriate HDMI to DVI-D cables or adapters are required for DVI signal input/output.

Video

Routing

DXP 44 HDMI	4 x 4 matrix
DXP 48 HDMI	4 x 8 matrix
DXP 84 HDMI	8 x 4 matrix
DXP 88 HDMI	8 x 8 matrix

Signal type	TMDS digital RGB and single-link DVI digital video signals are supported
Digital video	RGB digital video (DVI and HDMI standards) or Y, Cr, Cb digital component video (HDMI), actively buffered (supports all single-link DVI and HDMI [if using an optional adapter] standards from 640x480 @ 60 Hz to 1600x1200 @ 60 Hz computer video and HDTV 480p, 720p, 1080i, 1080p)

NOTE: The DXP HDMI Series switchers support HDMI specification features including data rates up to 6.75 Gbps, Deep Color up to 12-bit, 3D, and HD lossless audio formats.

Digital audio	Supports HDMI audio transmitted through the RGB and Y, Cr, Cb lines, actively buffered.
Consumer Electronics Control (CEC)	Not supported
EDID and DDC	Supports Extended Display Identification Data (EDID) and Display Data Channel (DDC) data using DVI and HDMI standards. EDID and DDC signals are actively buffered.
HDCP	Compliant with High-bandwidth Digital Content Protection (HDCP) using DVI and HDMI standards
HPD	Supports hot plug detection (HPD) of display as a pass-through signal.
Gain	Unity
Resolution range	Up to 1080p (HDTV) or 1920x1200 (the highest resolution of the single-link DVI standard) @ 60 Hz
Maximum data rate	6.75 Gbps (2.25 Gbps per color)
Maximum pixel clock	225 MHz
Standards	DVI 1.0, HDMI
Switching speed	200 ns, max.

Video input

Number/signal type	4 or 8 (depending on model) digital RGB (TMDS) HDMI (or single-link DVI-D*)
Connectors	4 or 8 female HDMI type A (digital only)
Nominal level	
Digital video	1.2 Vp-p
DDC (Display Data Channel)	5.0 Vp-p (TTL)
Minimum/maximum level	0.5 V to 1.0 Vp-p with no offset
Impedance	100 ohms
Return loss	<-15 dB @ 1 MHz to 1.5 GHz
TDR rise time (10%-90%)	75 ps
Equalization	Automatic

Input cable length >100' (30 m) at 1920x1200 @ 48, 50, or 60 Hz; or 1080p; 8 bit color

NOTE: The transmission distance varies depending on the signal resolution and on the type of cable, graphic card, and display used in the system.

Video output

Number/signal type 4 or 8 (depending on model) digital RGB
Connectors 4 or 8 female HDMI type A
Nominal level 1.2 Vp-p
Minimum/maximum level(s)..... 0.5 V to 1.0 Vp-p with no offset (follows input)
Impedance 100 ohms
Return loss <-15 dB @ 1 MHz to 1.5 GHz
DC offset ±500 mV maximum with input at 0 offset
Rise and fall time (20-80%)..... 0.6 ns
Re-clocking Automatic
Peripheral device power 250 mA per output

Control/remote — switcher

Serial control port..... (1) RS-232, 9-pin female D connector
(1) RS-232, front panel 2.5 mm mini stereo jack
Baud rate and protocol..... 9600 to 115200 baud, 9600 baud (default), 8 data bits, 1 stop bit, no parity
Serial control pin configurations
 9-pin D connector..... 2 = Tx, 3 = Rx, 5 = GND
 Mini stereo jack Tip = Tx, ring = Rx, sleeve = GND
Ethernet control port..... (1) RJ-45 female connector
Ethernet data rate 10/100Base-T, half/full duplex with autodetect
Ethernet protocol ARP, ICMP (ping), IP, TCP, DHCP, HTTP, Telnet
Default settings..... Link speed and duplex level = autodetected
IP address = 192.168.254.254
Subnet mask = 255.255.0.0
Gateway = 0.0.0.0
DHCP = off
Program control Extron control/configuration program for Windows®
Extron Simple Instruction Set (SIS™)
Microsoft® Internet Explorer® ver. 6 or higher, Telnet

General

Power supply..... Internal
Input: 100-240 VAC, 50-60 Hz
Power consumption 48 watts, fully loaded 8 x 8 unit
Temperature/humidity Storage: -40 to +158 °F (-40 to +70 °C) / 10% to 90%, noncondensing
Operating: +32 to +122 °F (0 to +50 °C) / 10% to 90%, noncondensing
Cooling..... Fan, air flows right to left (as viewed from front)
Thermal dissipation, full load..... 164 BTU/hr
Mounting
 Rack mount Yes, 2U high
Enclosure type..... Metal
Enclosure dimensions 3.5" H x 17.5" W x 12.0" D (2U high, full rack wide)
(8.9 cm H x 44.4 cm W x 30.5 cm D)
(Depth excludes connectors. Width excludes integrated rack ears.)
Product weight..... 10.0 lbs (4.5 kg)
Shipping weight..... 15 lbs (7 kg)
Vibration ISTA 1A in carton (International Safe Transit Association)

Regulatory compliance

Safety CE, c-UL, UL

Compliances CE, C-tick, FCC Class A, ICES, VCCI

Warranty 3 years parts and labor

NOTE: All nominal levels are at $\pm 10\%$.

NOTE: Specifications are subject to change without notice.

8.0-011812-D81" " " " #

For further resources and
documentation please visit us:
www.cinos.net