



# Archived resources

For further resources and  
documentation please visit us:  
**[www.cinos.net](http://www.cinos.net)**



# EYE-LCD-7000-HDMI

70" LCD MONITOR



## ) DISPLAY CHARACTERISTICS

- Professional 70 inch LCD-Monitor with S-PVA TFT-Display Panel
- Full HD Resolution (1920x1080px)
- 16:9 Aspect Ratio / Landscape or Portrait Installation
- Various Input Possibilities
- Metal Standard Chassis (standard black RAL9005, different RAL colours available on request)
- Different Installation Possibilities
- Optional with High Quality Speakers

## ) TECHNICAL SPECIFICATIONS

### LCD PANEL

|                        |                                 |
|------------------------|---------------------------------|
| Technology:            | S-PVA LCD                       |
| Max. Image Resolution: | 1,920 × 1,080 (full HD)         |
| Colours:               | 16.7M (8bits-true)              |
| Viewing Angle:         | 178° / 178°                     |
| Response Time          | 8 ms (Grey-to-Grey)             |
| Contrast Ratio:        | 2.000:1                         |
| Brightness:            | 600 cd/m <sup>2</sup> (Typical) |
| Pixel Pitch:           | 0.807 (H) × 0.807 (V) mm        |

### CONNECTORS & CONTROL

|         |   |
|---------|---|
| Inputs: | <ul style="list-style-type: none"> <li>1× Display Port up to 2560x1600 (60Hz), HDCP support</li> <li>2× HDMI 1.3, True High Definition 1080p, HDCP support</li> <li>1× RGB (15-pin H-DSUB female), captures up to 205MHz, Supports up to 1792x1344@60Hz or 1920x1260@60Hz or 1600x1200@75Hz standard modes</li> <li>1× Video Input, supports Composite Video, S-Video, and Component Video</li> <li>1× 3G-HD-SDI input (optional)</li> <li>1× RS232 Serial Port</li> <li>1× Audio In (L/R Cinch)</li> </ul> |
|---------|---|

### POWER SUPPLY

|                    |  |
|--------------------|--|
| Input Voltage:     | 100-250V 50/60Hz; Integrnal Power Supply |
| Power Consumption: | 700 Watt (max. 1000 Watt)                |

### ENVIRONMENTAL

|              |                   |
|--------------|-------------------|
| Temperature: | 0-40°C (<50%RH)   |
| Humidity:    | 20-80%RH (T<40°C) |

### MECHANICAL

|                     |                             |
|---------------------|-----------------------------|
| Screen Area:        | 1594.44 × 871.56 mm         |
| Dimensions (W×H×D): | 1677.7 × 1002 × 151.5 mm    |
| Bezel:              | 40 mm top/bottom/left/right |
| Weight:             | 95 kg                       |

### OPTIONS

|                |  |
|----------------|--|
| Audio:         | High Quality Speakers + integr. Amplifier  |
| Touch:         | Optical Touch Surface                      |
| Installations: | Different wall mounts and stands available |



#### eyevis GmbH

Hundsschleestr. 23 • 72766 Reutlingen • Germany  
 Phone: + 49 (0) 7121 43303 - 0 • Fax: + 49 (0) 7121 43303 - 22  
 www.eyevis.de • info@eyevis.de  
 As at: 23.10.2013/V1.4 • Subject to change!  
 All trademarks and registered trademarks are the property of their respective owners. Copyright © 2011 eyevis GmbH. All rights reserved.

For further resources and  
documentation please visit us:  
**[www.cinos.net](http://www.cinos.net)**