



Archived resources

For further resources and
documentation please visit us:
www.cinos.net



EYE-LCD-8200-HDMI

82" LCD MONITOR



) DISPLAY CHARACTERISTICS

- Professional 82 inch LCD-Monitor with S-PVA TFT-Display Panel
- Full HD Resolution (1920x1080px)
- 16:9 Aspect Ratio / Landscape or Portrait Installation
- Various Input Possibilities
- Metal Standard Chassis (standard black RAL9005, different RAL colours available on request)
- Different Installation Possibilities
- Optional with High Quality Speakers

) TECHNICAL SPECIFICATIONS

LCD PANEL

Technology:	S-PVA LCD
Max. Image Resolution:	1,920 × 1,080 (full HD)
Colours:	16.7M (8bits-true)
Viewing Angle:	178° / 178°
Response Time	8 ms (Grey-to-Grey)
Contrast Ratio:	2.000:1
Brightness:	600 cd/m ² (Typical)
Pixel Pitch:	0.9405 (H) × 0.9405 (V) mm

CONNECTORS & CONTROL

Inputs:	<ul style="list-style-type: none"> 1× Display Port up to 2560x1600 (60Hz), HDCP support 2× HDMI 1.3, True High Definition 1080p, HDCP support 1× RGB (15-pin H-DSUB female), captures up to 205MHz, Supports up to 1792x1344@60Hz or 1920x1260@60Hz or 1600x1200@75Hz standard modes 1× Video Input, supports Composite Video, S-Video, and Component Video 1× 3G-HD-SDI input (optional) 1× RS232 Serial Port 1× Audio In (L/R Cinch)
---------	---

POWER SUPPLY

Input Voltage:	100-250V 50/60Hz; Integrnal Power Supply
Power Consumption:	950 Watt (max. 1400 Watt)

ENVIRONMENTAL

Temperature:	0-40°C (<50%RH)
Humidity:	20-80%RH (T<40°C)

MECHANICAL

Screen Area:	1808 × 1016 mm
Dimensions (W×H×D):	1926 × 1137 × 150 mm
Bezel:	top/bottom 60,5mm, right/left 59 mm
Weight:	110 kg

OPTIONS

Audio:	High Quality Speakers + integr. Amplifier
Touch:	Optical Touch Surface
Installations:	Different wall mounts and stands available



eyevis GmbH

Hundsschleestr. 23 • 72766 Reutlingen • Germany
 Phone: + 49 (0) 7121 43303 - 0 • Fax: + 49 (0) 7121 43303 - 22
 www.eyevis.de • info@eyevis.de
 As at: 23.10.2013/V1.2 • Subject to change!
 All trademarks and registered trademarks are the property of their respective owners. Copyright © 2011 eyevis GmbH. All rights reserved.

For further resources and
documentation please visit us:
www.cinos.net